

Website:www.casainc.com Contact Phone Number: 888-257-3857

Service Contact:service@casainc.com

INDUSTRIAL BRIDGE KITCHEN FAUCET INSTALLATION INSTRUCTIONS

Notes before installation:

- 1.Please check that all components are present.
- 2.Before installation ensure that all feed lines are clear of debris and on/off valve is present.
- 3.Ensure water pressure is between 20-125 PSI (includes combination 3.DO NOT use caustic cleaning products as the use will break down of hot and cold feed lines).
- 4. Pictures in the manual are general in content and may not represent exactly your purchased faucet. If you are having difficulties please contact us.
- 5. If you will be away from home for an extended period you should shut off the main water supply.

Daily maintenance:

- 1. Use a soft cloth and vinegar to remove hard-water spots.
- 2.Check aerator(if present) regularly for calcium build up When water stream is not optimum.
- finish and will void the product warranty.
- 4. Acceptable cleaners include vinegar or mild non-abrasive liquid detergents.
- 5. If the water pressure appears to be less than optimum remove, inspect, clean or replace aerator.


Tools we will need:



Adjustable Wrench



Philips Screwdriver




1. Remove the rubber washer. metal washer and locking nut from the faucet. Install faucet through center hole




2.Re-install the rubber washer followed by the metal washer and lock-nut.Hand tighten then tighten further using a screw driver to tighten lock-nut screws




3.Install quick connector. Install the weight ball to pull-down hose in place.



4. Attach flexible hose to water supply.



5.Remove the sprayer head and turn on faucet for 1-minute to flush debris.



6.Close the handle and re-assemble sprayer head.

Note: Pictures in the manual are general in content and may not represent exactly your purchased faucet. If you have any questions, please feel free to contact us.