

InfiniSolar V IV



- Customizable status LED ring with RGB lights
- Touchable button with 4.3" colored LCD
- Supports USB On-the-Go function
- Data log events stored in the inverter
- Self-consumption and Feed-in to the grid
- Programmable supply priority for PV, Battery or Grid
- User-adjustable charging current and voltage
- Programmable multiple operation modes: Grid-tie, off-grid and grid-tie with backup
- Built-in Wi-Fi for mobile monitoring (App is available)
- Reserved communication port for BMS
- Parallel operation up to 9 units

InfiniSolar V IV On-Grid Inverter with Energy Storage Selection Guide

MODEL	InfiniSolar V IV 3.6KW	InfiniSolar V IV 5.6KW	InfiniSolar V IV 6KW
PHASE	1-phase in / 1-phase out		
MAXIMUM PV INPUT POWER	5000W	6000W	6500W
RATED OUTPUT POWER	3600W	5600W	6000W
MAXIMUM CHARGING POWER	5000W	6000W	6000W
GRID-TIE OPERATION			
PV INPUT (DC)			
Nominal DC Voltage / Maximum DC Voltage	360 VDC / 500 VDC	360 VDC / 450 VDC	360 VDC / 500 VDC
Start-up Voltage / Initial Feeding Voltage	110VDC / 120 VDC	110VDC / 120 VDC	120VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 430 VDC	120 VDC ~ 430 VDC	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1 / 18 A	1 / 27 A	1 / 27A
GRID OUTPUT (AC)			
Nominal Output Voltage	220/230/240 VAC		
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC (Selectable)		
Nominal Output Current	15.6A	24.3A	26.1A
Power Factor	> 0.9		
EFFICIENCY			
Maximum Conversion Efficiency (DC/AC)	96%	96%	95%
OFF-GRID OPERATION			
AC INPUT			
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC		
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC		
Maximum AC Input Current	40 A	40 A	40 A
PV INPUT (DC)			
Maximum DC Voltage	500 VDC	450 VDC	500 VDC
MPP Voltage Range	120 VDC ~ 430 VDC	120 VDC ~ 430 VDC	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1 / 18 A	1 / 27 A	1 / 27 A
BATTERY MODE OUTPUT (AC)			
Nominal Output Voltage	220/230/240 VAC		
Output Waveform	Pure sinewave		
Efficiency (DC to AC)	93%	93%	93%
HYBRID OPERATION			
PV INPUT (DC)			
Nominal DC Voltage / Maximum DC Voltage	360 VDC / 500 VDC	360 VDC / 450 VDC	360 VDC / 500 VDC
Start-up Voltage / Initial Feeding Voltage	110VDC / 120 VDC	110VDC / 120 VDC	120VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 430 VDC	120 VDC ~ 430 VDC	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1 / 18 A	1 / 27 A	1 / 27A
GRID OUTPUT (AC)			
Nominal Output Voltage	220/230/240 VAC		
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC (Selectable)		
Nominal Output Current	15.6A	24.3A	26.1A
AC INPUT			
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC		
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC		
Maximum AC Input Current	40A	40A	40A
BATTERY MODE OUTPUT (AC)			
Nominal Output Voltage	220/230/240 VAC		
Efficiency (DC to AC)	93%	93%	93%
BATTERY & CHARGER			
Nominal DC Voltage	48 VDC	48 VDC	48 VDC
Maximum Solar Charging Current	100A	120A	120A
Maximum AC Charging Current	100A	120A	120A
Maximum Charging Current	100A	120A	120A
GENERAL			
PHYSICAL			
Dimension, D x W x H (mm)	140 x 295 x 468		
Net Weight (kgs)	11	12	12
INTERACE			
Parallel Function	Yes, 9 units		
Communication Port	USB/RS232/RS485/Wifi/Dry-contact		
ENVIRONMENT			
Humidity	0 ~ 90% RH (Non-condensing)		
Operating Temperature	-10 to 50°C		

Product specifications are subject to change without further notice.