





(Figure7-1)

(Figure 7-2)

(Figure 7-3)

Pay attention to:

(1) The piston is numbered 123, Different sizes of spring slots, Need to remove one and install it and then remove the other. Avoid confusing locations, The air flow is blocked, It can't make a sound.

②Remove and install piston as little as possible

3> Attached tube

Need to pull out the attached tube one by one and wipe them clean, Add a little oil and smear evenly,



And then carefully install it.(Figure 8)

(Figure 8)

Pay attention to:

1)When pulling out the tuning tube, left hand holding musical instrument, Hold the tuning tube with your right hand, Avoid damaging the instrument when pulling it out.

2When pulling out the third accessory tube, Loosen the screws first, Then pull out the third attachment

3Minimize disassembly and assembly of the second auxiliary tube.

Clean the surface

After the performance, Wipe the outer surface of the instrument with a soft cotton cloth. Reduce the corrosion ofsweat on musical instruments, This can prolong the use of the instrument.(Figure 9)



(Figure9)

Note: The circle in the table is the number of keys that should be pressed

Means pressing the piston

O Do not press the piston

Use

Musical notation	Transform fingering	Basic fingering	e	
‡ .		•••	#	
5 #5 6		• 0 •	d	
ф		• • 0	†	
တ	•00	0 • •	φI	
		000	#	
7		0 • 0	0	
_		000	ф	
#		• • •	#	
N		• 0 •	0	
#6 7 1 #1 2 #2 3 4 #4 5		••0	# O O # O O # O O # O	
ω	•00	0 • •	ф	Ш
4		000	0	
#4	•••	0 • 0	Ö	Ш
Ŋ	• 0 •	000	¢	Щ
^{#5} 6 ^{#6} 7		• • 0	7	
တ	•00	0 • •		
_წ		00•	1	5
7	• 0 •	0 • 0		ф
<u></u> ٠٠	••0	000		0
#1 2 #2 3 4	•00	0 • •		Ö
N·	• 0 •	00•		ф
ι	••0	0 • 0		**
ω.	0 • •	000		0
•4		00•		
#.		0 • 0		<u> </u>
21.	• 0 •	000		
		• • 0		Ö
တ.	•00	0 • •		Шф #
ტ.		00•		 ‡
7		0 • 0		þ
٠٠.		000		

Fesley Trumpet, Cornetto, Tenor bugle, fingering table



Brand introduction

At FESLEY, we believe that anyone passionate about music deserves a high-quality instrument that is designed for beginners. Our team of experienced product designers is dedicated to crafting instruments that are not only practical and fashionable, but also have a professional timbre that delivers an exceptional musical experience.

We have partnered with factories that produce instruments for some of the most renowned brands to ensure our products are built to the highest quality, but without the high price tag. With FESLEY, beginners can enjoy similar quality as instruments worth thousands of dollars, at a fraction of the price.

Our mission is simple: to help music beginners develop their talents and achieve their dreams, without breaking the bank. Join us on our journey to create exceptional musical experiences that inspire creativity and passion in everyone.

Safety Precautions

Attention, children

When using oil and brightener to care for the instrument, Preventchildren from putting them in their mouths.

Instruments vary greatly with temperature. Please keep away from fire and high temperature objects,

Please take care of the instrument

This manual applies to products

Bb the trumpet

Bb cornetto

Pocket trumpet in Bb key

Trumpet structure diagram



Please read the installation instructions carefully

1>Install mouthpiece

left hand holding musical instrument, Right hand mounted mouthpiece, so as not to fall off easily.(Figure 1)



(Figure 1)

2> Adjustable ring


According to hand size and comfort, Adjust the distance of the ring, Lock when it feels right (Figure 2)



(Figure2)

3> The tuning

Because the tone changes with temperature, Therefore, the length of the pipe body can be changed by pulling out the main tuning pipe. The tuning.(Figure 3)



(Figure3)

Disassemble

1>After the performance, unplug the mouthpiece. Then press the valve to let off water.Let the remaining water droplets flow out. (Figure 4, Figure 5)



(Figure 4)



(Figure 5)

2>Unused time, Place it as shown in the figure.(Figure 6)



(Figure 6)

Maintenance instructions

1> Mouthpiece

Do not tap hard when installing the mouthpiece Avoid being too tight to pull out. If it cannot be pulled out, it needs to get a mechanic to look at it. 2>Piston

When the piston does not slide flexibly, First unscrew the top cover, Remove the piston body, Wipe with a clean cloth. Apply a little oil and spread evenly, Clean the inside of the piston sleeve, Install the piston body and rotate it for several turns, Remove the piston body when it feels flexible, Clean the piston body and the inner bore of the piston sleeve, Then install the piston body so that the spring retainer fits into the groove (Figure 7-1 Figure 7-2 Figure 7-3)